



TOLL FREE 1-800-392-0146

www.hoist-parts.com
parts@sisscohoist.com

SISSCO ONLINE HOIST PARTS DISTRIBUTION CENTER MANUALS



A Reputation for Service Since 1972
Certified WBE





K Series Stations — Polypropylene Enclosure

One-Speed and Two-Speed Control

Catalog Number	Description	Enclosure Size
Complete Pendant Stations		
Each station includes switches listed plus a standard package of legend plates (see page 6), Neoprene multi-step cord grip, strain relief bracket and Neoprene boots.		
K2-1	Two One-Speed Switches	Two-Button
K2-2A	Two Two-Speed Switches	Two-Button
K2-1M	Two One-Speed Switches with K-6A1 Maintained On/Off Switch	Two-Button
K2-2AM	Two Two-Speed Switches with K-6A1 Maintained On/Off Switch	Two-Button
K4-1	Four One-Speed Switches	Four-Button
K4-2A	Four Two-Speed Switches	Four-Button
K4-1M	Four One-Speed Switches with K-6A1 Maintained On/Off Switch	Four-Button
K4-2AM	Four Two-Speed Switches with K-6A1 Maintained On/Off Switch	Four-Button
K6-1	Six One-Speed Switches	Six-Button
K6-2A	Six Two-Speed Switches	Six-Button
K6-1M	Six One-Speed Switches with K-6A1 Maintained On/Off Switch	Six-Button
K6-2AM	Six Two-Speed Switches with K-6A1 Maintained On/Off Switch	Six-Button



Enclosures

Each complete enclosure includes a standard package of legend plates (see page 6), Neoprene multi-step cord grip, strain relief bracket and Neoprene boots.

K-2	Two-Button plus Accessory Space
K-4	Four-Button plus Accessory Space
K-6	Six-Button plus Accessory Space

Switches

RB-1	One-Speed Switch (with one set normally open and one set normally closed contacts)
RB-2A	Two-Speed Switch (one set normally closed and two normally open cumulative type "Make-Make" contacts)
K-1A	SPST, N/O Contact Momentary Switch
RPS-6	On/Off Toggle Switch with Neoprene Boot
K-6A1	Maintained Push-On/Push-Off Switch (includes push On/Off legend plate and Red Neoprene Boot)
PB-STA	Momentary On/Off Switch, Two Buttons, One Hole (NEMA 1 and 2)
PB-STMA	Maintained On/Off Switch, Two Buttons, One Hole (NEMA 1 and 2)

Catalog Number

Accessories

RPS-7	Key Switch (NEMA 1 and 2)
RPS-PL	Pilot Light, 115 VAC (NEMA 1 and 2)
KW-2	Black Neoprene Boot
KW-2R	Red Neoprene Boot
K-CG-B-2	Black Neoprene Multi-Step Cord Grip Boot, for .420 to .695 Diameter Cable
K-CG-B-3	Full Top Shroud Boot for .420 to .695 Diameter Cable. Recommended for outdoor or wet environments.
PT-7	Key Switch
PT-11	Two-Way Selector Switch (A-B)
PT-12	Three-Way Selector Switch (A-Both-B)
PT-16	Three Way Positive Selector Switch (A-Off-B)
PT-STMM	Mushroom Emergency On/Off Switch

RB-1 and RB-2A Switch Ratings	
Voltage	AC Amps
28	10
125	10
*Switches Not Suitable for DC Circuits	

Dimensions and Weights					
Enclosure Size	Dimensions — Inches			Weight Lbs.	Accommodates Cable Diameter (Inches*)
	Width	Depth	Length		
Two-Button	3-1/2	2-1/4	8-1/4	7/8	.420-.695
Four-Button	3-1/2	2-1/4	12	1-1/8	.420-.695
Six-Button	3-1/2	2-1/4	15	1-1/2	.420-.695