



TOLL FREE 1-800-392-0146

www.hoist-parts.com
parts@sisscohoist.com

SISSCO ONLINE HOIST PARTS DISTRIBUTION CENTER MANUALS



A Reputation for Service Since 1972
Certified WBE





RPB Series Stations — Rubber Enclosure

One-Speed and Two-Speed Control

Catalog Number	Description	Enclosure Size
Complete Pendant Stations		
Each station includes switches listed plus a standard package of legend plates (see page 6), cord grip and strain relief bracket.		
RPB -1-1	Two One-Speed Switches	Two-Button
RPB-1-2A	Two Two-Speed Switches	Two-Button
RPB-1-1M	Two One-Speed Switches with RPB-6A1 Maintained On/Off Switch	Four-Button
RPB-1-2AM	Two Two-Speed Switches with RPB-6A1 Maintained On/Off Switch	Four-Button
RPB-2-1	Four One-Speed Switches	Four-Button
RPB-2-2A	Four Two-Speed Switches	Four-Button
RPB-2-1M	Four One-Speed Switches with RPB-6A1 Maintained On/Off Switch	Six-Button
RPB-2-2AM	Four Two-Speed Switches with RPB-6A1 Maintained On/Off Switch	Six-Button
RPB-3-1	Six One-Speed Switches	Six-Button
RPB-3-2A	Six Two-Speed Switches	Six-Button
RPB-3-1M	Six One-Speed Switches with RPB-6A1 Maintained On/Off Switch	Eight-Button
RPB-3-2AM	Six Two-Speed Switches with RPB-6A1 Maintained On/Off Switch	Eight-Button
RPB-4-1	Eight One-Speed Switches	Eight-Button
RPB-4-2A	Six Two-Speed Switches and Two One-Speed Switches	Eight-Button



Enclosures

Each complete enclosure includes a standard package of legend plates (see page 6), cord grip and strain relief bracket.

RP-1	Two-Button
RP-2	Four-Button
RP-3	Six-Button
RP-4	Eight-Button

Front Covers Only (including Legend Plate Package)

RP-1F	Two-Button
RP-2F	Four-Button
RP-3F	Six-Button
RP-4F	Eight-Button

Switches

RB-1	One-Speed Switch (with one set normally open and one set normally closed contacts)
RB-2A	Two-Speed Switch (one set normally closed and two normally open cumulative type "Make-Make" contacts)
RPB-6A1	Maintained Push-On/Push-Off Switch (push ON/OFF legend plate will be furnished)

RB-1 and RB-2A Switch Ratings	
Voltage	AC Amps
28	10
125	10
*Switches Not Suitable for DC Circuits	

Catalog Number

Accessories

RPB-TS	Duplex Tie Straps (must be factory-installed)
RPB-MG-1	Wire Mesh Grip for Two-, Four-, and Six-Button Stations
RPB-MG-1C	Complete Wire Mesh Cord Grip (including connector and bushing) 3/4" NPS (specify cable O.D.)
RPB-MG-2	Wire Mesh Grip for Eight-Button Station
RPB-MG-2C	Complete Wire Mesh Cord Grip (including connector and bushing) 1" NPS (specify cable O.D.)

Dimensions and Weights

Enclosure Size	Dimensions — Inches			Weight Lbs.	Accommodates Cable Diameter (Inches*)
	Width	Depth	Length		
Two-Button	3	2-1/2	5-3/4	1-3/4	.437-.740
Four-Button	3	2-1/2	9	2-3/4	.437-.740
Six-Button	3	2-1/2	12-3/8	3-1/2	.437-.740
Eight-Button	3	2-5/8	15-3/4	4-1/4	.640-.875
* Specify Cable Diameter when the Cable Used is not within the Range Listed.					