



TOLL FREE 1-800-392-0146

www.hoist-parts.com
parts@sisscohoist.com

SISSCO ONLINE HOIST PARTS DISTRIBUTION CENTER MANUALS



A Reputation for Service Since 1972
Certified WBE





RPS Series Stations — Rubber Enclosure

One-Speed through Five-Speed Control

Catalog Number	Description
----------------	-------------

Complete Pendant Stations

Each station includes switches listed plus a standard package of legend plates (see page 6), cord grip, strain relief bracket and Neoprene boots.

Six-Button Stations

RPS-3-1A	3-Motion – All One-Speed with Blank Acces. Area
RPS-3-3A	3-Motion – All Three-Speed with Blank Acces. Area
RPS-3-5A	3-Motion – All Five-Speed with Blank Acces. Area

Eight-Button Stations

RPS-4-1A	4-Motion – All One-Speed
RPS-4-3A	4-Motion – All Three-Speed
RPS-4-5A	4-Motion – All Five-Speed

Enclosures

Each enclosure includes a standard package of legend plates (see p. 6), cord grip, strain relief bracket and Neoprene boots. The top accessory area on these enclosures will accept any two-button inserts or any two accessories.

RPS-3	Eight-Button
--------------	--------------

Two-Button Inserts

PB Switch Rating: 1 Amp per Contact, 125VAC. NEMA 4.

PB-1A	One-Speed Insert
PB-1B	One-Speed Insert with Mechanical Interlock
PB-3A	Three-Speed Cumulative Insert
PB-3B	Three-Speed Cumulative Insert with Mechanical Interlock
PB-5A	Five-Speed Cumulative Insert
PB-5B	Five-Speed Cumulative Insert with Mechanical Interlock
PB-ST	Momentary On/Off with Red and Black Neoprene Boots
PB-BBM	Two-Speed Non-Cumulative Insert — “Break-Before-Make” action. For mechanical interlock, add “-B”.
PB-STM	Maintained On/Off

Accessories and Replacement Parts

(All Switches Rated NEMA 4 Except as Noted)

RPS-6	On/Off Toggle Switch with Neoprene Boot
RPS-7	Key Switch (NEMA 1 and 2)
RPS-7X	Key Switch (NEMA 4)
RPS-PL	Pilot Light, 115 VAC (NEMA 1 and 2)
RPS-PLA	Pilot Light, 115 VAC with Full Shroud
RPS-11	Two-way Selector Switch, Function A, B
RPS-10	Three-way Selector Switch, Function A, B, Both
RPS-12	Three-way Selector Switch, Function A, Both, B
RPS-MS	Momentary Push Button with Black Neoprene Boot
PB-STA	Momentary Start/Stop with Two Buttons (One Hole, NEMA 1 and 2)
PB-STMA	Maintained Start/Stop with Two Buttons (One Hole, NEMA 1 and 2)
PB-STB	Momentary Start/Stop with Two Buttons (One Hole)

Note: Catalog numbers listed include standard switches. To specify mechanical interlock switches, change the “A” suffix to “B”.



Catalog Number	Description
----------------	-------------

Accessories and Replacement Parts (Cont.)

PB-STMM	Maintained On/Off with Mushroom Head, Pull-On/Push-Off Action
J-RPS-TS	Duplex Tie Straps (must be factory-installed)
RPS-MG	Wire Mesh Grip
RPS-MG-C	Complete Wire Mesh Cord Grip (including connector and bushing) 1-1/4" NPS (specify cable O.D.)
PBW-3	Black Neoprene Boot
PBW-3R	Red Neoprene Boot

Dimensions and Weights

Enclosure	Dimensions — Inches			Weight Lbs.	Accommodates Cable Diameter (Inches*)
	Width	Depth	Length		
RPS-3	4	2-1/2	20	7-3/4	.688-1.250