



**TOLL FREE 1-800-392-0146**

[www.hoist-parts.com](http://www.hoist-parts.com)  
[parts@sisscohoist.com](mailto:parts@sisscohoist.com)

**SISSCO ONLINE HOIST PARTS DISTRIBUTION CENTER MANUALS**



***A Reputation for Service Since 1972***  
***Certified WBE***





# J Series Stations — Polypropylene Enclosure

## One-Speed through Five-Speed Control

### Catalog Number

### Description

#### Complete Pendant Stations

Each station includes switches listed plus a standard package of legend plates (see page 6), cord grip, strain relief bracket and Neoprene boots. Order On/Off switches separately by the catalog number listed below under Accessories and Replacement Parts.

- J6-2-1A** 2-Motion—All One-Speed
- J6-2-3A** 2-Motion—All Three-Speed
- J6-2-5A** 2-Motion—All Five-Speed
- J8-3-1A** 3-Motion—All One-Speed
- J8-3-3A** 3-Motion—All Three-Speed
- J8-3-5A** 3-Motion—All Five-Speed
- J10-4-1A** 4-Motion—All One-Speed
- J10-4-3A** 4-Motion—All Three-Speed
- J10-4-5A** 4-Motion—All Five-Speed

**Note:** Catalog numbers listed include standard switches. To specify mechanical interlock switches, change the "A" suffix to "B".

#### Enclosures

Each enclosure includes a standard package of legend plates (see p. 6), cord grip, strain relief bracket and Neoprene boots. The top accessory area on these enclosures will accept any two-button inserts or any two accessories. The J7, J9 and J11 enclosures will also accept any one accessory in the bottom position.

- J-6** Six-Button
- J-7** Seven-Button
- J-8** Eight-Button
- J-9** Nine-Button
- J-10** Ten-Button
- J-11** Eleven-Button

#### Two-Button Inserts

PB Switch Rating: 1 Amp per Contact, 125VAC, NEMA 4.

- PB-1A** One-Speed Insert
- PB-1B** One-Speed Insert with Mechanical Interlock
- PB-3A** Three-Speed Cumulative Insert
- PB-3B** Three-Speed Cumulative Insert with Mechanical Interlock
- PB-5A** Five-Speed Cumulative Insert
- PB-5B** Five-Speed Cumulative Insert with Mechanical Interlock
- PB-ST** Momentary On/Off with Red and Black Neoprene Boots
- PB-BBM** Two-Speed Non-Cumulative Insert — "Break-Before-Make" action. For mechanical interlock, add "-B".
- PB-STM** Maintained On/Off

#### Accessories and Replacement Parts

(All switches Rated NEMA 4 Except as Noted)

- RPS-6** On/Off Toggle Switch with Neoprene Boot
- RPS-7** Key Switch (NEMA 1 and 2)
- RPS-7X** Key Switch (NEMA 4)
- RPS-PL** Pilot Light, 115 VAC (NEMA 1 and 2)
- RPS-PLA** Pilot Light, 115 VAC with Full Shroud
- RPS-11** Two-way Selector Switch, Function A, B
- RPS-10** Three-way Selector Switch, Function A, B, Both
- RPS-12** Three-way Selector Switch, Function A, Both, B
- RPS-MS** Momentary Horn Button with Black Neoprene Boot
- PB-STA** Momentary Start/Stop with Two Buttons (One Hole, NEMA 1 and 2)
- PB-STMA** Maintained Start/Stop with Two Buttons (One Hole, NEMA 1 and 2)
- PB-STB** Momentary Start/Stop with Two Buttons (One Hole)
- PB-STMB** Maintained Start/Stop with Two Buttons (One Hole)



### Catalog Number

### Description

#### Accessories and Replacement Parts (Cont.)

- PB-STMM** Maintained On/Off with Mushroom Head, Pull-On/Push-Off Action
- J-RPS-TS** Duplex Tie Straps (must be factory-installed)
- RPS-MG** Wire Mesh Grip
- RPS-MG-C** Complete Wire Mesh Cord Grip (including connector and bushing) 1-1/4" NPS (specify cable O.D.)
- PBW-3** Black Neoprene Boot
- PBW-3R** Red Neoprene Boot

#### Dimensions and Weights

Enclosure Catalog Number	Dimensions — Inches			Weight Lbs.	Accommodates Cable Diameter (Inches*)
	Width	Depth	Length		
J-6	3-3/4	3-3/4	16	2-1/2	.688 - .1.250
J-7	3-3/4	3-3/4	18	2-5/8	.688 - .1.250
J-8	3-3/4	3-3/4	20	3	.688 - .1.250
J-9	3-3/4	3-3/4	21-3/4	3-1/4	.688 - .1.250
J-10	3-3/4	3-3/4	24	3-1/2	.688 - .1.250
J-11	3-3/4	3-3/4	25-3/4	3-3/4	.688 - .1.250